



**1. ELECTRICAL TEST:**

- (1).100% OPEN SHORT & MISS WIRE TEST;
- (2). INSULATION RESISTANCE:DC 250V 20M OHM MIN;
- (3). CONTACTOR RESISTANCE:30 OHM MAX

2. PRINTING:GHMT® roline CAT.6A S/FTP COMPONENT PATCH CORD LSZH 500MHZ ISO/IEC

11801 & EN 50173-1 & ANSI/TIA-568-C.2

3.100% Component Patch cord Test PASS

4. Minimum bending radius:60mm

**MATERIAL LIST**

⑥	LABEL	NO DRY GLUE LABEL	1PCS	
⑤	MINI TIE	PE MINI TIE(POSSESS METAL)	2PCS	
④	POLYETHYLENE BAG	POLYETHYLENE BAG	1PCS	
③	OVER MOLD	88A PVC Brown	2PCS	
②	CONNECTOR	RJ45 8P8C'S SHIELDED PIN GOLD PLATED 3u", SHELL PLATED NICKEL Transparent Blue	2PCS	
①	CABLE	S/FTP CAT. 6A 26AWG (BC*1P+AL-FOIL)*4P+BRAID CABLE JACKET LSOH OD=6.2±0.2MM	1PCS	
NO.	PARTS NAME	SPECIFICATION STANDARD	QT' Y	REMARK

COLOUR:Brown (PANTONE:463C)					
ITEM NO.	LENGTH (L)	TOLERANCE (T)			
21. 15. 2978	300mm	± 10mm			
21. 15. 2880	500mm	± 15mm			
21. 15. 2881	1000mm	± 30mm			
21. 15. 2884	1500mm	± 45mm			
21. 15. 2882	2000mm	± 60mm			
21. 15. 2883	3000mm	± 90mm			
21. 15. 2885	5000mm	± 150mm			
21. 15. 2886	7500mm	± 210mm			
21. 15. 2887	10000mm	± 300mm			
21. 15. 2888	15000mm	± 450mm			
21. 15. 2889	20000mm	± 600mm			
ITEM NO.	21. 15. 2978	21. 15. 2880	21. 15. 2881	21. 15. 2882	21. 15. 2883
21. 15. 2884	21. 15. 2885	21. 15. 2886	21. 15. 2887	21. 15. 2888	21. 15. 2889
DESC.	ROLINE S/FTP PatchCord CAT. 6A, LSOH, Comp. Level1, Brown				



		NEW		2016-09-13	A
BY	CHK	REVISION RECORD MODIFICATIONS		DATE	REV.